

CAR / TRUCK > CAR / TRUCK - MATERIAL AND ACCESSORIES FOR REPAIR



GO-SEAL SAFETY SEALANT

Code: **MRI05BXXX0009**

Safety Wheel 2 is a water-based liquid tyre sealant. It is applied to the tyre as a preventive measure against punctures. Safety Wheel 2 spreads itself in an even film around the tyre's inner liner and therefore does not affect the tyre's balance. If an object punctures the tyre, the damage is sealed immediately without loss of air pressure. Can seal punctures, including cuts up to 16 mm long, and can be easily washed from inside the tyre if reinforcements need to be applied. Safety Wheel 2 Tyre Sealant can be used in all types of air-filled tyres on both road and off-road vehicles, as well as tyres of smaller ride-on or hand operated vehicles. Typical uses are: trucks, construction machinery/equipment, mobile cranes, agricultural machinery, forestry machinery, forklifts, ATVs/quad-bikes, grounds-care machines in addition to all sorts of smaller wheels such as ride-on lawnmowers, wheelbarrows, walking frames, wheelchairs, etc. (max speed 90 km/h, 55 mph).

Safety Wheel 2 contains no substances that are harmful to the environment and ...

ALSO AVAILABLE THE PUMP FOR THE GO-SEAL SEALING SAFETY

TOSI SNC